





NOTES:

1. ASSEMBLE CONNECTOR INTERFACE IN ACCORDANCE WITH MIL-STD-348.

2. MATERIAL: BODY & HEX NUT- BRASS PER ASTM B16

CONTACT - BRASS PER ASTM B16
INSULATOR - TEFLON PER ASTM D1710
GASKET - SILICONE RUBBER PER ZZ-R-765
CLAMP & CLAMP NUT - BRASS PER ASTM B16
WASHERS & HALF WASHER - BRASS PER ASTM B16
SPRINGWASHER - BERYLLIUM COPPER PER ASTM B196

BAYONET SLEEVE - BRASS PER ASTM B196

3. FINISHES: CONTACT - SILVER PLATE PER QQ-S-365

UNLESS OTHERWISE SPECIFIED: TOLERANCES: 3 PLACES = ±.005,

ALL OTHER METAL PARTS - NICKLE PER QQ-N-290

	_	OUTLINE	8/11/08	20
ANGLES = $\pm 1/2$	ALT.	REVISIONS	DATE	٥
				П

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS MFG CORP. AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT THEIR EXPRESS WRITTEN CONSENT.

2 PLACES = $\pm .02$.

DELTA ELECTRONICS MFG. CORP. Beverly, MA 01915

"BNC" PLUG FOR RG-5, 61/U CABLE

:0DE ||DENT.-00795 | 1001—001—N000—1