





## NOTES:

1. ASSEMBLED CONNECTOR INTERFACE IS DESIGNED IN ACCORDANCE WITH MIL-STD-348.

2. MATERIAL: CONTACT — BRASS PER ASTM B16.

INSULATOR - TEFLON PER ASTM D4894

SPRING WASHERS - BERYLLIUM COPPER PER ASTM B196

GASKET — SILICONE RUBBER PER A—A—59588 ALL OTHER METAL PARTS — BRASS PER ASTM B16

UNLESS OTHERWISE SPECIFIED: TOLERANCES: 3 PLACES =  $\pm .005$ , 2 PLACES =  $\pm .02$ , ANGLES =  $\pm 1/2$ \*, SURFACE FINISH

3. FINISHES: CONTACT - GOLD PLATE PER ASTM B488

ALL OTHER METAL PARTS - SILVER PLATE PER ASTM B700

	-	OUTLINE	12/23/02	Draw	
= 63	ALT.		DATE	1:	
	•				

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS MFG CORP. AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT THEIR EXPRESS WRITTEN CONSENT.

M39012/16-0225

	DELTA	ELECTRONIC	CS MFG. C	ORP. Bev	verly, MA 01915	
					G-8A, 9B,	
		B7A, 213	, 214 &	225/U	CABLES	
/02	Drawn by BJM	Scale	Ckd. by	Engr Appd	FILE NAME: 1001004A00E-00	
	DUNI	2/1	MR	MR	1001004A00E-00	TOC

12/23/02	2/ 1	IVIT	IVIT	100100 111002 000
CODE IDEI	VT -00795	100	0.000	04-A00E