





NOTES:

1. ASSEMBLED CONNECTOR INTERFACE IS DESIGNED IN ACCORDANCE WITH MIL-STD-348.

2. MATERIAL: BODY - BRASS PER ASTM B16

CONTACT - BRASS PER ASTM B16. INSULATOR - TEFLON PER ASTM D1710

GASKET - SILICONE RUBBER PER ZZ-R-765

3. FINISHES: BODY - NICKEL PLATE PER QQ-N-290

CONTACT - SILVER PLATE PER QQ-S-365

UNLESS OTHERWISE SPECIFIED: TOLERANCES: 3 PLACES = ±.005, 2 PLACES = $\pm .02$. ANGLES = $\pm 1/2^{\circ}$

9/29/10 OUTLINE REVISIONS

Drawn by BJM 9/29/10

Scale 2/1

Ckd. by

TITLE: 'BNC' (M) CLAMP PLUG FOR RG-8A, 9B,

UG-959A/U

DELTA ELECTRONICS MFG. CORP. Beverly, MA 01915

B7A, 213, 214 & 225/U CABLES

Engr Appd MR

FILE NAME: 1001004N000-000T

1001004N000-000

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS MFG CORP. AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT THEIR EXPRESS WRITTEN CONSENT.