





NOTES:

1. ASSEMBLED CONNECTOR INTERFACE IS DESIGNED IN ACCORDANCE WITH MIL-STD-348.

2. MATERIAL: CONTACT - BRASS PER ASTM B16.

INSULATOR — TEFLON PER ASTM D4894
SPRING WASHERS — BERYLLIUM COPPER PER ASTM B196
GASKET — SILICONE RUBBER PER A—A—59588
ALL OTHER METAL PARTS — BRASS PER ASTM B16

3. FINISHES: CONTACT - GOLD PLATE PER ASTM B488

ı		Δ	II OTHER	OTHER METAL PARTS -		SILVER PLATE PER ASTM		R700			
			LL OTTLIN	WEIAE TAINS	SILVEI	V I DAIL I LIV	ASTIVI	B700	ı	OUTLINE	4/26/0
	UNLESS (OTHERWISE S	SPECIFIED:	TOLERANCES: 3 PLACE	$ES = \pm .005,$	2 PLACES = :	±.02,	ANGLES = $\pm 1/2^{\circ}$	ALT.	REVISIONS	DATE

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS MFG CORP. AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT THEIR EXPRESS WRITTEN CONSENT.

M39012/16-0101

DELTA	A ELECTRONICS	MFG. COR	P. Beverly,	MA 01915
TITLE:	'BNC' CLAM	1P PLUG	FOR RG-	-55B.

58C, 141A, 142B, & 223/U CABLES

	,							
6	Drawn by	Scale	Ckd. by	Engr Appd	FILE	NAME:		
	4/26/06	4/1	MR	MR		1001015A00E-000T		
	CODE IDENT00795		10	01-0	15-	-A00E		