



NOTES:

1. ASSEMBLED CONNECTOR INTERFACE IS DESIGNED IN ACCORDANCE WITH MIL-STD-348.

UG-88C/U

2. MATERIAL: CONTACT - BRASS PER ASTM B16. INSULATOR - TEFLON PER ASTM D1710 GASKET - SILICONE RUBBER PER ZZ-R-765 ALL OTHER METAL PARTS - BRASS PER ASTM B16

3. FINISHES: CONTACT - SILVER PLATE PER QQ-S-365

ALL PLATED PARTS - NICKEL PLATE PER QQ-N-290

UNLESS OTHERWISE SPECIFIED: TOLERANCES: 3 PLACES = ±.005. ANGLES = $\pm 1/2^{\circ}$ $2 \text{ PLACES} = \pm .02.$

OUTLINE 2/24/99 DATE

•	Drawn by BJM 2/24/99	Scal 4/
_		

TITLE:

Ckd. by Engr Appd MR MR

FILE NAME: 1001015N000-001T

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS MFG CORP. AND SHALL NOT BE REPRODUCED. OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT THEIR EXPRESS WRITTEN CONSENT.

1001-015-N000-

DELTA ELECTRONICS MFG. CORP. Beverly, MA 01915

'BNC' (M) CLAMP PLUG FOR RG-55B,

58C, 141A, 142B, & 223/U CABLES