





NOTES:

1. ASSEMBLED CONNECTOR INTERFACE IN ACCORDANCE WITH MIL-STD-348.

2. MATERIALS: GASKETS — SILICONE RUBBER PER ZZ-4-765 INSULATORS — TEFLON PER ASTM D1710

SPRING WASHERS — BERYLLIUM COPPER PER ASTM B196

ALL OTHER METAL PARTS - BRASS

UNLESS OTHERWISE SPECIFIED: TOLERANCES: 3 PLACES = ±.005,

3. FINISHES: BODY AND HARDWARE - NICKEL PLATE PER QQ-N-290

CONTACT - SILVER PLATE PER QQ-S-365

				'
	-	OUTLINE	10/16/13	Drawn by
±1/2*	ALT.	REVISIONS	DATE	10/16/13

TITLE: "BNC" CAPTIVE CONTACT PLUG FOR RG-59B,
62A, 71B, 140B & 210B/U CABLE

713 Drawn by Scale Ckd. by Engr Appd FILE NAME:
10/16/13 4/1 BJM BJM 1001021N004-000T

UG-260/U

DELTA ELECTRONICS MFG. CORP. Beverly, MA 01915

CODE IDENT.-00795

1001024N001-000

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS MFG CORP. AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT THEIR EXPRESS WRITTEN CONSENT.

 $2 PLACES = \pm .02.$

ANGLES =