



## NOTES:

1. ASSEMBLED CONNECTOR INTERFACE IS DESIGNED IN ACCORDANCE WITH MIL-STD-348.

2. MATERIAL: BODY & BAYONET SLEEVE- BRASS PER ASTM B16

CONTACT & SPRING WASHER - BERYLLIUM COPPER PER ASTM B196.

INSULATORS - TEFLON PER ASTM D1710 GASKET - SILICONE RUBBER PER ZZ-R-765 CRIMP SLEEVE - D.H.P. COPPER CDA ALLOY 122

3. FINISHES: CONTACT (LOOSE) - GOLD PLATE PER MIL-G-45204 CONTACT (INTERNAL) - SILVER PLATE PER QQ-S-365

CRIMP SLÈEVE - SULFAMATE NICKEL PLATE PER MIL-P-27418 ALL OTHER PLATED PARTS - NICKEL PLATE PER QQ-N-290

|  | -    | OUTLINE   | 11/30/05 | B |
|--|------|-----------|----------|---|
| UNLESS OTHERWISE SPECIFIED: TOLERANCES: 3 PLACES = ±.005, 2 PLACES = ±.02, ANGLES = ±1/2', SURFACE FINISH = 63 | ALT. | REVISIONS | DATE     | Ľ |

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS MFG CORP. AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT THEIR EXPRESS WRITTEN CONSENT.

| DELTA ELECTRONICS MFG. CORP. | Beverly, MA 01915 |
|------------------------------|-------------------|
|------------------------------|-------------------|

TITLE: 'BNC' CRIMP PLUG FOR RG-174, 179B, 187A, 188A & 316 CABLES

| Drawn by<br>BJM<br>11/30/05 | Scale<br>4/1 | Ckd. by<br><b>MR</b> | Engr Appd<br>MR | FILE NAME:<br>1003037N000-000T |  |
|-----------------------------|--------------|----------------------|-----------------|--------------------------------|--|
| 0000 100                    |              |                      |                 |                                |  |

CUDE IDENI.-00795 | 1003-037-N000