





NOTES:

1. ASSEMBLED CONNECTOR INTERFACE IS DESIGNED IN ACCORDANCE WITH MIL-STD-348.

2. MATERIAL: INSULATORS — TEFLON PER ASTM D1710
GASKET — SILICONE RUBBER PER ZZ—R—765
CONTACT — BERYLLIUM COPPER PER ASTM B196

ALL OTHER METAL PARTS - BRASS PER ASTM B16

UNLESS OTHERWISE SPECIFIED: TOLERANCES: 3 PLACES = \pm .005, 2 PLACES = \pm .02, ANGLES = \pm 1/2*, SURFACE FINISH

3. FINISHES: CONTACT - SILVER PLATE PER QQ-S-365 ALL OTHER METAL PARTS - NICKEL PLATE PER QQ-N-290

		-	OUTLINE	8/28/06	٦
-	63	ALT.	REVISIONS	DATE	L
					Г

	TITLE:		BNC'	JACK		
	FOR RO	G-59B, 6	2A, 71B	, 140 8	½ 210/U	CABLES
)6	Drawn by DG	Scale	Ckd. by	Engr Appd	FILE NAME	
-	8/28/06	4/1	MR	MR	1008021N000-002T	
	CODE IDENT00795		1008-021-N000-2			

UG-261C/U

DELTA ELECTRONICS MFG. CORP. Beverly, MA 01915

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS MFG CORP. AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT THEIR EXPRESS WRITTEN CONSENT.