



NOTES:

1. ASSEMBLED CONNECTOR INTERFACE IS DESIGNED IN ACCORDANCE WITH MIL-STD-348.

2. MATERIAL: CONTACT — BERYLLIUM COPPER PER ASTM B196. INSULATOR — TEFLON PER ASTM D1710 CRIMP SLEEVE — D.H.P. COPPER CDA ALLOY 122

UNLESS OTHERWISE SPECIFIED: TOLERANCES: 3 PLACES = ±.005, 2 PLACES = ±.02,

ALL OTHER METAL PARTS - BRASS PER ASTM B16

3. FINISHES: CONTACT & BUSHING - SILVER PLATE PER QQ-S-365 ALL OTHER METAL PARTS - NICKEL PLATE PER QQ-N-290

4. RECOMMENDED CRIMP TOOL M22520/5-19 CLOUSURE A (.250 HEX DIA)

A REVISED 9/2/97

- OUTLINE 5/8/89

ANGLES = ±1/2* ALT. REVISIONS DATE

WANG 350-2201

	DELTA ELECTRONICS MFG. CORP. Beverly, MA 01915				
	TITLE:	'BNC' SI	HORT CI	RIMP JAC	CK FOR
,	RG-59/U CABLE				
,	Drawn by M.IA	Scale	Ckd. by	Engr Appd	FILE NAME:
•	Drawn by MJA 9/2/97	Scale 4/1	Ckd. by	Engr Appd	FILE NAME: 1010020N001-001T

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS MFG CORP. AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT THEIR EXPRESS WRITTEN CONSENT.