





NOTES:

- 1. ASSEMBLED CONNECTOR INTERFACE IS DESIGNED IN ACCORDANCE WITH MIL-STD-348.
- 2. MATERIAL: BODY, BAYONET SLEEVE, HALF WASHERS BRASS PER ASTM B16

CONTACT & FINGERS - BRASS PER ASTM B16.

UNLESS OTHERWISE SPECIFIED: TOLERANCES: 3 PLACES = $\pm .005$, 2 PLACES = $\pm .02$, ANGLES = $\pm 1/2$ °, SURFACE FINISH = 63

SPRING WASHER - BERYLLIUM COPPER PER ASTM B196.

GASKET - SILICONE RUBBER PER ZZ-R-765

INSULATORS - TEFLON PER ASTM D1710

3. FINISHES: CONTACT - SILVER PLATE PER QQ-S-365

ALL OTHER METAL PARTS - NICKEL PLATE PER QQ-N-290

-	OUTLINE	6/26/06	Drawn by
_т.	REVISIONS	DATE	6/26/06

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS MFG CORP. AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT THEIR EXPRESS WRITTEN CONSENT.

UG-1104 A/U

6	Drawn by	Coalo	Cled by	Engr Annd	ELLE NAME.	
	/ V	VITH CAPT	IVE SOLI	DER POT	CONTACT	
	TITLE:	'BNC' PA				
						<u> </u>
	I I)FI IA	FLECTRONIC	S MEG. C	ORP. Bev	verly, MA 0191	5

6	Drawn by DG 6/26/06	Scale 4/1	Ckd. by MR	Engr Appd MR	l	NAME: 1023000N180)-002T
	ממחב וחב	UT AAZAE	4.00	7 00		1400)

CODE IDENT.-00795 | 1023-000-N180-2