



— 1.203 REF — - .425 -.090 -.045 MIN .260 MAX PANEL THICKNESS -3/8-32 UNEF-2A THREAD

OUTLINE

DATE

VIEW SHOWN WITH HEX. NUT & LOCKWASHER REMOVED

NOTES:

1. ASSEMBLED CONNECTOR INTERFACE IS DESIGNED IN ACCORDANCE WITH MIL-STD-348.

2. MATERIAL: BODY & HEX NUT- BRASS PER ASTM B16

LOCKWASHER - SPRING STEEL

CONTACT - BERYLLIUM COPPER PER ASTM B196.

BUSHING - BRASS PER ASTM B16.

GASKET - SILICONE RUBBER PER ZZ-R-765

INSULATOR - TEFLON PER ASTM D1710

3. FINISHES: CONTACT - GOLD PLATE PER MIL-G-45204

ALL OTHER METAL PARTS - SILVER PLATE PER QQ-S-365

UNLESS OTHERWISE SPECIFIED: TOLERANCES: 3 PLACES = ±.005, 2 PLACES = ±.02, ANGLES = ±1/2, SURFACE FINISH = 63

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS MFG CORP. AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT THEIR EXPRESS WRITTEN CONSENT.

M39012/24-0002

DELTA	ELECTRONICS MFG. CORP. Beverly, MA 01915
TITLE:	'BNC' STRAIGHT BUI KHEAD JACK

RECEPTACLE-REAR MOUNT, HERMETIC SEALED

4/10/07 Drawn by DG Scale Ckd. by Engr Appd FILE NAME: 4/1 1047000A63F-000T MR 4/10/07

1047-000-A63F