



NOTES:

1. ASSEMBLED CONNECTOR INTERFACE IS DESIGNED IN ACCORDANCE WITH MIL-STD-348.

2. MATERIAL: BODY - BRASS PER ASTM B16

CONTACT - BERYLLIUM COPPER PER ASTM B196.

INSULATOR - TEFLON PER ASTM D1710

3. FINISHES: BODY - NICKEL PLATE PER QQ-N-290

CONTACT - GOLD PLATE PER MIL-G-45204

4. CONTACT TO WITHSTAND A 6 LB AXIAL FORCE AND 4 IN-OZ TORQUE.

	_	OUTLINE	6/14/05
UNLESS OTHERWISE SPECIFIED: TOLERANCES: 3 PLACES = ±.005, 2 PLACES = ±.02, ANGLES = ±1/2', SURFACE FINISH = 63	ALT.	REVISIONS	DATE

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS MFG CORP. AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT THEIR EXPRESS WRITTEN CONSENT.

DELTA ELECTRONICS MFG. CORP. Beverly, MA 01915

TITLE: 'BNC' PANEL MOUNTED RECEPTACLE JACK - FPOXY CAPTIVE

′05 E	Drawn by BJM 6/14/05	Scale 4/1	Ckd. by MR	Engr Appd MR	FILE NAME: 1058000N181-001T

CODE IDENT.-00795 | 1058-000-N181-1