



## NOTES:

1. ASSEMBLED CONNECTOR INTERFACE IS DESIGNED IN ACCORDANCE WITH MIL-STD-348.

2. MATERIAL: BODY - BRASS PER ASTM B16

CONTACT - BERYLLIUM COPPER PER ASTM B196.

INSULATOR - TEFLON PER ASTM D1710

3. FINISHES: BODY - NICKEL PLATE PER QQ-N-290

CONTACT - GOLD PLATE PER MIL-G-45204

I	UNLES	S 01	THER	WISE	SPEC	CIFIED:	TOL	ERAN	ICES: 3	5 PLA	CES	= ±	.005	5,	2 P	LACES	= :	±.02,		ANGLE	S = ±	:1/2*		ALT.	RE	EVISIONS	DA
I		THESI	E DRA	AWINGS	AND	SPECIF	FICATIO	NS A	ARE TH	E PR	ROPER	RTY (	OF	DELTA	A ELE	CTRON	IICS	MFG (	CORP	. AND	SHALL	NOT	BE F	REPRODU	JCE	O, OR COPI	ED
۱			OR L	JSED A	AS THE	BASIS	FOR	THE	MANU	FACTL	JRE (	OR S	SALE	OF	APPA	RATUS	OR	DEVIC	ES V	VITHOU	T THE	R EXF	PRESS	WRITTE	IN C	CONSENT.	

OUTLINE

		DELIA ELECTRONICS WITO. CORT. DEVELTY, WIA 01313												
		TITLE: "N	l" PANEL	MOUNT	JACK RI	ECEPTACLE								
		SLOTTED CONTACT												
	10/23/09	Drawn by <b>MR</b>	Scale	Ckd. by	Engr Appd	FILE NAME:								
	DATE	10/23/09	4/1	ВЈМ	MR	1143000N091-003T								
-	IED	CODE IDE	NT00795	1143-000-N091-3										

DELTA ELECTRONICS MEG CORP Reverly MA 01915