



- NOTES:
1. INTERFACE IS IN ACCORDANCE WITH MIL-STD-348.
  2. MATERIAL: BODY-BRASS PER ASTM B 16, CONTACT-BERYLLIUM COPPER PER ASTM B 196, INSULATOR-TEFLON PER ASTM D 1710, O-RING-SILICONE RUBBER PER ZZ-R-765.
  3. FINISH: BODY-NICKEL PLATE PER QQ-N-290, CONTACT GOLD PLATE PER MIL-G-45204.

LB./M	FT./M	Stock Size
TOLERANCES: UNLESS OTHERWISE SPECIFIED; DECIMALS = ±.005, FRACTIONS = ±1/64, ANGLES = ±1/2° REMOVE ALL BURRS AND SHARP EDGES.		
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS MFG. CORP. AND SHALL NOT BE REPRODUCED, OR COPIED, OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT THEIR EXPRESS WRITTEN CONSENT.		

OUTLINE	1-29-96	ENGR APPD	MFG APPD
ALT.	REVISIONS	DATE	
FILE NAME: 114000N091-059T PLT @ 4/1			

DELTA ELECTRONICS MFG. CORP. Beverly, MA 01915				
TITLE: "N" (F) PANEL RECEPTACLE - POST WITH EXTENDED INSULATOR, O-RING				
MATERIAL: SEE NOTE 2				
FINISH: SEE NOTE 3				
Drawn by MR	Scale 4/1	Ckd. by	Mfg. Appd.	Engr. Appd.
1-29-96				
CODE IDENT-00795		1143-000-N091-59		