





NOTES:

1. ASSEMBLED CONNECTOR INTERFACE IS DESIGNED IN ACCORDANCE WITH MIL-STD-348.

2. MATERIAL: BODY - BRASS PER ASTM B16

CONTACT - BERYLLIUM COPPER PER ASTM B196.

INSULATOR - TEFLON PER ASTM D1710

UNLESS OTHERWISE SPECIFIED: TOLERANCES: 3 PLACES = ±.005, 2 PLACES = ±.02,

3. FINISHES: BODY - NICKEL PLATE PER QQ-N-290

CONTACT - GOLD PLATE PER MIL-G-45204

	A	REVISED	2/24/97	
	ı	OUTLINE	2/5/97	
ANGLES = $\pm 1/2^{\circ}$	ALT.	REVISIONS	DATE	

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS MFG CORP. AND SHALL NOT BE I	REPRODU	CED, OR COPIED
OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT THEIR EXPRESS	WRITTEN	N CONSENT.

DELTA ELECTRONICS MFG. CORP. Beverly, MA 01915								
"N"(F) PANEL MOUNT RECEPTACLE EXTENDED INSULATOR / POST CONTACT								
Drawn by MR 2/5/97	Scale 2/1	Ckd. by	Engr Appd	FILE NAME: 1143000N091-069T				
CODE IDE	CODE IDENT00795 1143-000-NOS)-N091-69				