



NOTES:

1. ASSEMBLED CONNECTOR INTERFACE IS DESIGNED IN ACCORDANCE WITH MIL-STD-348.

2. MATERIAL: BODY - BRASS PER ASTM B16

CONTACT - BERYLLIUM COPPER PER ASTM B196.

INSULATOR - TEFLON PER ASTM D1710

3. FINISHES: BODY - NICKEL PLATE PER QQ-N-290

CONTACT - GOLD PLATE PER MIL-G-45204

UNLESS OTHERWISE SPECIFIED: TOLERANCES: 3 PLACES = $\pm .005$, 2 PLACES = $\pm .02$, ANGLES = $\pm 1/2^{\circ}$

LES:	S OTI	HERWISE	SPE	CIFIED:	TOLE	RANCE	S: 3	PLACES	=	±.00	5,	2 PL	ACES =	±.02,		ANGLE:	S = ±	1/2*		ALT.	REV	ISIONS	3
	THESE	DRAWING	S AND	SPECIF	ICATION	S ARI	E THE	PROPE	ERTY	OF	DELT	A ELEC	TRONICS	MFG	COR	P. AND	SHALL	NOT	BE	REPRODU	JCED,	OR C	OP
		OP LISED	AC TH	E DACIC	EOP T	UC 14	ANITEA	CTUDE	ΛP	CAL	- 0-	ADDAD	THE A	0 054	ICEC	WITHOU	T TUC10	- EVE	DEC	C WOITTE	N CO	NICENIT	г

REVISED

OUTLINE

12/18/97

DATE

	D	ELTA ELECT	RONICS	MFG. COR	P. Beverl	y, MA 01915	
	TITLE:	"N" (F) PANE	EL MOU	NT RECE	PTACLE	
1/25/02		EXTEND	EĎ INSL	JLATOR	/ POST	CONTACT	

12/18/97 4/1	Drawn by MJA 12/18/97	Scale 4/1	Ckd. by	Engr Appd	FILE NAME: 1143000N091-075T
----------------	-----------------------------	--------------	---------	-----------	--------------------------------

CODE IDENT.-00795 1143-000-N091-75