





NOTES:

1. ASSEMBLED CONNECTOR INTERFACE IS DESIGNED IN ACCORDANCE WITH MIL-STD-348.

2. MATERIAL: BODY - BRASS PER ASTM B16

UNLESS OTHERWISE SPECIFIED: TOLERANCES: 3 PLACES = ±.005,

CONTACT - BERYLLIUM COPPER PER ASTM B196.

INSULATOR - TEFLON PER ASTM D1710

3. FINISHES: BODY - NICKEL PLATE PER QQ-N-290

CONTACT - GOLD PLATE PER MIL-G-45204

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS MFG CORP. AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT THEIR EXPRESS WRITTEN CONSENT.

 $2 PLACES = \pm .02$

ANGLES = $\pm 1/2^{\circ}$ ALT. REVISIONS DATE

P. AND SHALL NOT BE REPRODUCED, OR COPIED

OUTLINE

8/7/97

ALCATEL 500-11 W/EXCEPTIONS

DELTA ELECTRONICS MFG. CORP. Beverly, MA 01915

^{ILE:} 'N' (F) PANEL MOUNTED RECEPTACLE
WITH EXTENDED/SLOTTED CAPTIVE CONTACT

Drawn by Scale Ckd. by Engr Appd FILE NAME: 8/7/97 2/1 1143000N331-017T

CODE IDENT.-00795 | 1143-000-N331-17