



NOTES:

1. ASSEMBLED CONNECTOR INTERFACE IS DESIGNED IN ACCORDANCE WITH MIL-STD-348.

2. MATERIAL: BODY - BRASS PER ASTM B16

CONTACT- BERYLLIUM COPPER PER ASTM B196.

INSULATOR - TEFLON PER ASTM D1710

3. FINISHES: BODY - NICKEL PLATE PER QQ-N-290

CONTACT - GOLD PLATE PER MIL-G-45204

UNLESS OTHERWISE SPECIFIED: TOLERANCES: 3 PLACES = ±.005, 2 PLACES = ±.02. ANGLES = ±1/2*

	011	ILINIISL	٥,	LOI	TILD.	101		1020.		· D (OLO		1.000	<u>, </u>	Z T DAOLS		1.02,		WOLLS		/-		/ (INLVI	31014	٦	
Т	HESE	DRAWING	S A	ND S	SPECIFI	ICATIC	NS A	ARE	THE	PROP	ERTY	OF	DELTA	A ELECTRON	ICS	MFG	CORP.	AND	SHALL	NOT	BE	REPRODU	CED,	OR	COPI	ΞD
	0	R USED	AS T	THE	BASIS	FOR	THE	MAN	NUFA	CTURE	OR	SALE	OF	APPARATUS	OR	DEVIC	CES W	TUOHTI	THEIR	EXP	RESS	S WRITTEI	N CON	NSEN	IT.	

DELTA	ELECTRONIC	CS MFG. C	ORP. Bev	verly, MA 01915	
TITLE: 'TN			JACK F	RECEPTACLE IAL	
Drawn by BJM 2/6/09	Scale 4/1	Ckd. by MR	Engr Appd MR	FILE NAME: 1213000N180-000	т

CODE IDENT.-00795

2/6/09

OUTLINE

1213-000-N180