



NOTES:

- 1. ASSEMBLED CONNECTOR INTERFACE IS DESIGNED IN ACCORDANCE WITH MIL-STD-348.
- 2. MATERIAL: BODY & HEX COUPLING NUT- CORROSION RESISTANT STEEL PER ASTM A582

CONTACT - BERYLLIUM COPPER PER ASTM B196.

INSULATOR - TEFLON PER ASTM D4894

GASKET - SILICONE RUBBER PER A-A-59588

3. FINISHES: CONTACT - GOLD PLATE PER ASTM B488

CRIMP SLEEVE - SULFAMATE NICKEL PER MIL-P-27418

COUPLING NUT & BODY - PASSIVATE PER AMS-QQ-P-35

UNLESS OTHERWISE SPECIFIED: TOLERANCES: 3 PLACES = ±.005, 2 PLACES = ±.02, ANGLES = ±1/2', SURFACE FINISH = 63

4. DESIGNED IN ACCORDANCE WITH M39012/55

| E PERPONICED OR CORED | | | | AADE IDENT AAZAE | | 4707 047 1/005 | | | |
|-----------------------|------|-----------|---------|--|-------|----------------|-----------|----------------|----|
| | ALT. | REVISIONS | DATE | 3/28/07 | 4/1 | MR | MR | 1303017K00E-00 | от |
| | - | OUTLINE | 3/28/07 | Drawn by | Scale | Ckd. by | Engr Appd | FILE NAME: | |
| | | | | RG-58 & 303/U CABLES - CAPTIVE CONTACT | | | | | |
| | | | | '''LE: 'SMA' CRIMP PLUG FOR | | | | | |

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS MFG CORP. AND SHALL NOT BE REPRODUCED, OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT THEIR EXPRESS WRITTEN CONSENT. CODE IDEN 1.-00/95 I 1303-01/-K00E

M39012/55 - 3029

DELTA ELECTRONICS MFG. CORP. Beverly, MA 01915