





## NOTES:

1. ASSEMBLED CONNECTOR INTERFACE IS DESIGNED IN ACCORDANCE WITH MIL-STD-348.

2. MATERIAL: BODY - CORROSION RESISTANT STEEL PER ASTM A582

CONTACT - BERYLLIUM COPPER PER ASTM B196. INSULATOR - TEFLON PER ASTM D1710

3. FINISHES: BODY - PASSIVATE PER QQ-P-35

CONTACT - GOLD PLATE PER MIL-G-45204

UNLESS OTHERWISE SPECIFIED: TOLERANCES: 3 PLACES =  $\pm .005$ , 2 PLACES =  $\pm .02$ , ANGLES =  $\pm 1/2$ \*

= ±1/2\* ALT

- OUTLINE 8/7/97
ALT. REVISIONS DATE

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS MFG CORP. AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT THEIR EXPRESS WRITTEN CONSENT.

ALCATEL 500-02R

ı		ELECTRUNIC								
	TITLE: 'SM	A' (M) P	ANEL MO	UNTED	RECEPT	ACLE				
	TITLE: 'SMA' (M) PANEL MOUNTED RECEPTACLE WITH EXTENDED/SLOTTED NON-CAPTIVE CONTACT									
ı	Drawn by	Scalo	Ckd by	Engr Appd	FILE NA	ME				

DELTA ELECTRONICO MEC CORR. Dougly MA 01016

Drawn by RWP 8/7/97	Scale 4/1	Ckd. by	Engr Appd	FILE	NAME: 1359000K050	0-007T
לעטב וטב	NT OOZOE	175	0 00		L/OFO	

COUL IDENI.-00/95 | 1359-000-K050-7