



NOTES:

1. ASSEMBLED CONNECTOR INTERFACE IS DESIGNED IN ACCORDANCE WITH MIL-C-55235.
2. MATERIAL: BODY & HEX NUT - BRASS PER ASTM B16
CONTACT - BERYLLIUM COPPER PER ASTM B196.
INSULATOR - TEFLON PER ASTM D1710
GASKET - SILICONE RUBBER PER ZZ-R-765
LOCKWASHER - SPRING STEEL
3. FINISHES: ALL METAL PARTS - GOLD PLATED PER MIL-G-45204
4. RECOMMENDED TORQUE VALUE = 12-15 INCH-LBS.

UG-1365/U

DELTA ELECTRONICS MFG. CORP. Beverly, MA 01915

TITLE: TPS BULKHEAD JACK RECEPTACLE
- SOLDER POT CONTACT

UNLESS OTHERWISE SPECIFIED: TOLERANCES: 3 PLACES = $\pm .005$ 2 PLACES = $\pm .02$ ANGLES = $\pm 1/2^\circ$ SURFACE FINISH = 63	AL.T.	REVISIONS	DATE
-	OUTLINE	3/2/05	

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS MFG CORP. AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT THEIR EXPRESS WRITTEN CONSENT.

Drawn by BUM	Scale 4/1	Okd. by MR	Engr Appd MR	FILE NAME: 4420000661-000T
CODE IDENT. -00795				4420-000-6661