

NOTES:

1. ASSEMBLED CONNECTOR INTERFACE IS DESIGNED IN ACCORDANCE WITH MIL-STD-348(75 OHM BNC).

2. MATERIAL: BODY & HEX NUT - BRASS PER ASTM B16 CONTACT - BERYLLIUM COPPER PER ASTM B196 INSULATOR - TEFLON PER ASTM D1710

LOCKING WASHER - SPRING STEEL

3. FINISHES: CONTACT — GOLD PLATE PER MIL—G-45204 BODY & HEX NUT & WASHER — NICKEL PLATE PER QQ-N-290

3. FINISHES: CONTACT — GOLD PLATE PER MIL—G—45204 BODY & HEX NUT & WASHER — NICKEL PLATE PER QQ—N—290				J	
	-	OUTLINE	8/12/13	ľ	
UNLESS OTHERWISE SPECIFIED: TOLERANCES: 3 PLACES = ±.005, 2 PLACES = ±.02, ANGLES = ±1/2, SURFA	FACE FINISH = 63	ALT.	REVISIONS	DATE	Ľ
					1

DELTA ELECTRONICS MFG. CORP. Beverly, MA 01915

TITLE:

'BNC' 75 OHMS BULKHEAD MOUNT RECEPTACLE

Drawn by JAMES 8/12/13 Scale 4/1

Ckd. by Engr Appd BJM BJM

FILE NAME: 7521000N621-002T

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS MFG CORP. AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT THEIR EXPRESS WRITTEN CONSENT.

7521000N621-002